

Technical Specifications

Electrical	C-Band Linear	C-Band Circular	Ku-Band Linear
Antenna Size	1.8M (71 in.)	1.8M (71 in.)	1.8M (71 in.)
Operating Frequency (GHz)			
Receive	3.625 - 4.20 GHz	3.625 - 4.20 GHz	10.70 - 12.75 GHz
Transmit	5.85 - 6.425 GHz	5.85 - 6.425 GHz	13.75 - 14.50 GHz
Midband Gain (+/- .2dB)			
Receive	35.50 dBi	35.30 dBi	44.80 dBi
Transmit	39.50 dBi	39.30 dBi	46.80 dBi
Antenna Noise Temperature			
10° Elevation	45 K	45 K	69 K
20° Elevation	41 K	41 K	64 K
30° Elevation	41 K	41 K	63 K
40° Elevation	40 K	40 K	62 K
Sidelobe Envelope, Co-Pol (dBi)			
100λ/D ≤ θ ≤ 20°	29 - 25 Logθ dBi	29 - 25 Logθ dBi	29 - 25 Logθ dBi
20° < θ ≤ 26.3°	-3.5 dBi	-3.5 dBi	-3.5 dBi
26.3° < θ ≤ 48°	32 - 25 Logθ dBi	32 - 25 Logθ dBi	32 - 25 Logθ dBi
48° < θ	-10 dBi (averaged).	-10 dBi (averaged)	-10 dBi (averaged)
Cross-Pol Isolation (Linear)			
On Axis	30 dB	17.7 dB Tx 15.5 dB Rx	30 dB
With 1.0 dB Beamwidth	26 dB	17.7 dB Tx 15.5 dB Rx	26 dB
VSWR	1.3:1 Max.	1.3:1 Max.	1.3:1 Max. Tx 1.5:1 Max. Rx
Output Waveguide Interface Flange	WR137 or N Tx WR229 Rx	WR137 or N Tx WR229 Rx	WR75 WR229 Rx
Power Handling	1 kW	1 kW	100 W

Mechanical			
Reflector Material	Glass fiber reinforced polyester SMC		
Antenna Optics	Prime Focus, One-Piece, Offset Feed		
Mount Type	Elevation over Azimuth		
Mast Pipe Size	3.5" SCH 40 Pipe (4.0" OD) 10.16 cm.		
Elevation Adjustment Range	5° to 90°, Continuous Fine Adjustment		
Azimuth Adjustment Range	360° Continuous		
Shipping Specifications (Approx. Net Weight)	180 lbs. (82kg.)	185 lbs. (84kg.)	170 lbs. (78kg.)

Environmental Performance	
Wind Loading	
Operational	45 mph (72 km/h)
Survival	125 mph (201 km/h)
Temperature (operational)	
Operational	-40° to 140° F (-40° to 60° C)
Rain (operational)	
Operational	1/2" (13 mm)/hr
Ice	
Operational	-----
Atmospheric Conditions	Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas
Relative Humidity	0 to 100% With Condensation
Solar Radiation	360 BTU/h/ft ²