



## FEATURES

**Ultralinear**  
**Lightweight**  
**High Efficiency**  
**Broadband**



### STA5340 Ku series 400W Antenna Mount HPA

The STA5340 Ku series HPA provides ultra linear, high efficiency performance in a compact, lightweight, rugged, weatherproof, antenna mount enclosure. The advanced packaging and cooling techniques enable the unit to operate in extreme environmental conditions from direct rain to direct sunlight. The amplifiers can be simply deployed anywhere in the world, are user-friendly and incorporate a comprehensive remote control facility as standard, including RS485, RS232 and Ethernet options.

The HPA incorporates a high efficiency multi-collector TWT powered by an advanced power supply built on over 30 years of experience in the design and manufacture of satellite amplifiers.


The company's products have an enviable reputation for performance, robust quality and reliable service.

The STA5340 Ku is available with a wide range of options and accessories, backed by worldwide technical support.

### Features

- Advanced cooling design enables operation at +60°C and in direct sunlight
- Weatherproof antenna mount construction allows exposed mounting
- Ethernet/SMP/Webpage GUI interfaces
- Broadband – high efficiency operation
- CE compliant
- Wide input voltage range - can operate from mains supplies worldwide
- Redundant control - contains control and drive circuits for 1:1 redundancy
- Stand-alone setting - automatically sequences to transmit mode
- Wide range of accessories including: Controllers, waveguide networks, cable assemblies

## BLOCK DIAGRAM



### RF Performance:

Frequency	
KU1	13.75 – 14.50 GHz
KU2	12.75 – 14.50 GHz
KU3	13.75 – 14.80 GHz
KU4	12.75 – 13.25 GHz
Bandwidth	500 MHz / 750 MHz

Output Power	(for load VSWR $\leq$ 1.5:1)
TWT Power	56.0 dBm (400 W)
Rated (flange)	55.4 dBm (350 W) typical
Linear, $P_{LIN}$	49.5 dBm (90 W)
(with optional Linearizer)	52.5 dBm (180 W)

#### Gain

Gain	$\geq$ 70 dB
Variation, 80 MHz, $\Delta G_{80MHz}$	$\leq$ 0.8 dB peak-peak
Variation, 750 MHz, $\Delta G_{750MHz}$	$\leq$ 2.5 dB peak-peak
Slope, $\Delta G_{SLOPE}$	$\pm$ 0.04 dB/MHz
Gain Stability vs. Time @ constant drive & temp	$\pm$ 0.25 dB/24 hours
Gain Stability vs. Temperature @ constant drive & frequency	$\pm$ 1.0 dB
Adjustment range, $G_{ADJ}$	30.0 dB typical
Adjustment step size	0.1 dB

#### Linearity

AM/PM @ $P_o \leq P_{LIN} - 1dB$	$\leq$ 2.0°/dB
Inter-modulations (IMD) 2-tone	$\leq$ -28 dBc @ $P_o \leq P_{LIN} - 1 dB$
Spectral Re-growth (SR)	$\leq$ -30 dBc @ $P_o \leq P_{LIN} - 1 dB$
Noise Power Ratio (NPR)	$\leq$ -19 dBc @ $P_o \leq P_{LIN} - 1 dB$

Input VSWR (Return Loss)	$\leq$ 1.3:1 (17.7 dB)
Output VSWR (Return Loss)	$\leq$ 1.3:1 (17.7 dB)
Load VSWR (no damage)	$\leq$ 2.0:1 (9.5 dB)
Harmonic 2 <sup>nd</sup> & 3 <sup>rd</sup>	$\leq$ -60 dBc

#### Noise Power

Transmit Band ( $T_x$ )	$\leq$ -70 dBW/4KHz
Receive Band ( $R_x$ )	$\leq$ -150 dBW/4KHz (10.65 – 11.75/12.75 GHz)

Spurious @ $P_o \leq MLP$	$\leq$ -60 dBc
Residual AM	$\leq$ -50 dBc, $f < 10KHz$ $\leq$ -20(1.5+LOG(frequency KHz))dBc, $f = 10KHz$ to 500KHz $\leq$ -85 dBc >500KHz

Phase Noise	10 dB below IESS requirement $\leq$ - 50 dBc, AC fundamental $\leq$ - 47 dBc, Sum of all spurs
-------------	--

#### Group Delay (any 80 MHz)

Linear	0.01 nsec/MHz, max
Parabolic	0.005 nsec/MHz <sup>2</sup> , max
Ripple	0.5 nsec/Peak-Peak, max

### Prime Power:

AC Input Voltage	99-265 VAC $\pm$ 10%, single phase 50-60 Hz $\pm$ 5%
Full Load Current	12.5 A max @ 200 VAC
Power Consumption	1300 VA typical 1450 VA maximum
Power Factor	0.98 typical 0.96 minimum

### Environmental:

Ambient Temperature	-40°C to +60°C
Relative Humidity	100% condensing
Altitude	12,000 ft. with standard adiabatic de-rating of 2°C/1000 ft., operating  50,000 ft., non-operating
Shock	15 g peak, 11mSec, 1/2 sine
Vibration	3.2 g rms, 10-500 Hz
Acoustic Noise	65 dBA @ $\geq$ 3 ft. from amplifier
Solar Gain	1120 2/m <sup>2</sup>

### Mechanical:

Dimensions	Request outline
Length	52 cm
Width	26 cm
Height	26 cm
Weight	21 kg typical
RF Input	Type N(f) 50 ohm
RF Output	WR-75
RF Sample	Type N(f) 50 ohm
AC Input	Amphenol C016 20C003 200 12
Ethernet	RJF71B
M&C Connector	PT07E18-32S (MS3114E-18-32S)