



SPECS

WAVEGUIDE SIZE: WR229
 FREQUENCY: 3.3–4.9 GHZ
 VSWR: 1.25:1
 CONNECTOR: SMA, F OR M
 MATERIAL: 6061 ALUMINUM
 FINISH: BLUE ANODIZE

Type	Order Code
WR229 WG to coax adapter (F)	AST1061-2R-F (FEMALE CONNECTOR,CPRF FLANGE)
WR229 WG to coax adapter (M)	AST1061-2G-M (MALE CONNECTOR,CPRG FLANGE)

FLANGE CODES: CPRF=R, CPRG=G

STEP
ELECTRONICS
 A Division of Av-Comm

REVISIONS		APPROVALS			
SYM	DESCRIPTION	DATE	ENGRG	PROD	Q.A.

PROPRIETARY INFORMATION
 THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION WHICH SHALL NOT BE REPRODUCED, TRANSFERRED TO OTHER DOCUMENTS, DISCLOSED TO OTHERS, USED FOR MANUFACTURING OR ANY OTHER PURPOSE WITHOUT PRIOR WRITTEN PERMISSION FROM AST.

BREAK ALL CORNERS AND SHARP EDGES

UNLESS OTHERWISE SPECIFIED	DRAWN	WR229 WAVEGUIDE TO COAXIAL ADAPTER (SMA)	
FRACTIONAL ± 1/32	CHECKER		
DECIMAL .XXX ± .010	MECH. ENGR.		
ANGULAR .XX ± .020	ELEC. ENGR.		
	PROJ. ENGR.		
MATERIAL: NOTED SPEC:	CHIEF ENGR.	DRAWING # AST1061-2	
FINISH: NOTED SPEC:		SCALE NTS	SHEET 1 OF 1