



SPECS

WAVEGUIDE SIZE: WR284
 FREQUENCY: 2.6-3.95 GHZ
 VSWR: 1.25:1
 CONNECTOR: SMA, F OR M
 MATERIAL: 6061 ALUMINUM
 FINISH: BLUE ANODIZE

Type	Order Code
WR284 WG to coax adapter (F)	AST1061-1R-F (FEMALE CONNECTOR,CPRF FLANGE)
WR284 WG to coax adapter (M)	AST1061-1G-M (MALE CONNECTOR,CPRG FLANGE)

FLANGE CODES: CPRF=R, CPRG=G, COVER=F, CHOKE=K



REVISIONS		APPROVALS			
SYM	DESCRIPTION	DATE	ENGR	PROD	Q.A.

PROPRIETARY INFORMATION
 THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION WHICH SHALL NOT BE REPRODUCED, TRANSFERRED TO OTHER DOCUMENTS, DISCLOSED TO OTHERS, USED FOR MANUFACTURING OR ANY OTHER PURPOSE WITHOUT PRIOR WRITTEN PERMISSION FROM AST.

BREAK ALL CORNERS AND SHARP EDGES					
UNLESS OTHERWISE SPECIFIED	DRAWN				
FRACTIONAL ± 1/32	CHECKER				
DECIMAL .XXX ± .010	MECH. ENGR.				
ANGULAR .XX ± .020 ± 1/2°	ELEC. ENGR.				
MATERIAL: NOTED	PROJ. ENGR.				
SPEC:	CHEF ENGR.				
FINISH: NOTED					
SPEC:					
DRAWING # AST1061-1			SHEET 1 OF 1		
SCALE NTS			SHEET 1 OF 1		