



SPECS

WAVEGUIDE SIZE: WR62
 FREQUENCY: 12.4 – 18.0 GHZ
 VSWR: 1.25:1
 CONNECTOR: SMA F OR M
 MATERIAL: 6061 ALUMINUM
 FINISH: BLUE ANODIZE

Type	Order Code
WR62 WG to coax adapter (F)	AST1061-90-F (FEMALE CONNECTOR,UGG FLANGE)
WR62 WG to coax adapter (M)	AST1061-90-M (MALE CONNECTOR,UGG FLANGE)

FLANGE CODES: UGG=O, COVER=F, CHOKE=K



REVISIONS		APPROVALS			
SYM	DESCRIPTION	DATE	ENGRG	PROD	Q.A.

PROPRIETARY INFORMATION
 THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION WHICH SHALL NOT BE REPRODUCED, TRANSFERRED TO OTHER DOCUMENTS, DISCLOSED TO OTHERS, USED FOR MANUFACTURING OR ANY OTHER PURPOSE WITHOUT PRIOR WRITTEN PERMISSION FROM AST.

BREAK ALL CORNERS AND SHARP EDGES

UNLESS OTHERWISE SPECIFIED FRACTIONAL ± 1/32 DECIMAL .XXX ± .010 ANGULAR .XX ± .020 ± 1/2°	DRAWN		WR62 WAVEGUIDE TO COAXIAL ADAPTER (SMA)	DRAWING # AST1061-9	SHEET 1 OF 1
	CHECKER				
	MECH. ENGR.				
	ELEC. ENGR.				
MATERIAL: NOTED SPEC:	PROJ. ENGR.		SCALE NTS		
FINISH: NOTED SPEC:	CHIEF ENGR.				