



SPECS

WAVEGUIDE SIZE: WR75
 FREQUENCY: 10.0 – 15.0 GHZ
 VSWR: 1.25:1
 CONNECTOR: SMA F OR M
 MATERIAL: 6061 ALUMINUM
 FINISH: BLUE ANODIZE

Type	Order Code
WR75 WG to coax adapter (F)	AST1061-80-F (UGG FLANGE, FEMALE CONNECTOR)
WR75 WG to coax adapter (M)	AST1061-8G-M (CPRG FLANGE, MALE CONNECTOR)

FLANGE CODES: UGG=O, COVER=F, CPRF=R, CPRG=G, CHOKE=K, PDR=P



REVISIONS		APPROVALS			
SYM	DESCRIPTION	DATE	ENGRG	PROD	Q.A.

PROPRIETARY INFORMATION
 THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION WHICH SHALL NOT BE REPRODUCED, TRANSFERRED TO OTHER DOCUMENTS, DISCLOSED TO OTHERS, USED FOR MANUFACTURING OR ANY OTHER PURPOSE WITHOUT PRIOR WRITTEN PERMISSION FROM AST.

BREAK ALL CORNERS AND SHARP EDGES

UNLESS OTHERWISE SPECIFIED FRACTIONAL ± 1/32 DECIMAL .XXX ± .010 ANGULAR .XX ± 1/2°	NOT TO SCALE	DRAWN	
		CHECKER	
		MECH. ENGR.	
		ELEC. ENGR.	
MATERIAL: NOTED SPEC:		PROJ. ENGR.	
FINISH: NOTED SPEC:		CHEF ENGR.	

WR75 WAVEGUIDE TO COAXIAL ADAPTER (SMA)	
DRAWING # AST1061-8	
SCALE NTS	SHEET 1 OF 1